


DOUBLE DAM & TRIPLE DAM

WATER-INFLATED BARRIER SOLUTION

FOR FLOOD PROTECTION & CIVIL CONSTRUCTION COFFERDAMS



Double Dam & Triple Dam barriers are water inflated tube-like, deployable products made of industrial grade PVC. They are inflated using the water that you are working against and act like a dike or cofferdam for flood protection and/or diversion needs.



PART NO.	LENGTH	WIDTH	DRY WEIGHT
DD2450	50'	5'	120lbs
DD3650	50'	7.5'	180lbs
DD4850	50'	10'	230lbs
DD6050	50'	12.5'	320lbs
DD7250	50'	15.75'	405lbs
DD9650	50'	20.5'	520lbs

NOTES:

- 1) Double Dam and Triple Dam products are water-inflated dams suitable for use in flood mitigation and cofferdams in civil construction applications.
- 2) Double Dam and Triple Dam products are generally suitable for installation on dry surfaces, in standing waters or dynamic waters.
- 3) A completed site pre-evaluation worksheet(as provided by a factory authorized provider) is required to validate site suitability and warranty of all Double Dam installations.
- 4) All Triple Dam installations must be performed or supervised by a factory approved representative to validate warranty.
- 5) Double Dam and Triple Dam products are engineered to operate with a minimum 25% freeboard in static water applications. Dynamic water installations require additional freeboard.
- 6) Double Dams and Triple Dams can be filled with any available water source. 2" and 3" NPT fittings for fill and drain operations are standard on all units. Filling and draining time will vary with the size of the dam deployed and the volumetric capacity of the pump(s).
- 7) Double Dam and Triple Dam are intended for reuse. A factory authorized representative can provide direction for product recovery. Once recovery is complete, suitable storage must provide protection from exposure to outdoor elements and avoid extended exposure to temperatures above 100°F.

This data is provided for informational purposes only. Titan Environmental Containment Ltd. makes no warranties as to the suitability or the fitness for a specific use or merchantability of the products referred to, no guarantee of satisfactory results from reliance upon contained information or recommendations and disclaims all liability from resulting loss or damage. This information is subject to change without notice, please check with Titan Environmental Containment Ltd. for current updates.

Titan Environmental Containment

Toll free: 1-866-327-1957 | info@titanenviro.com | TitanEnviro.com