## **Titan RCG-24**

## 24 mil WOVEN COATED GEOMEMBRANE



Commonly used for interim landfill covers and short-term liners. Titan RCG-24 is a medium weight fabric incorporating a coating designed to improve toughness and abrasion resistance, and is intended for exposed applications up to 5 years.

## **PRODUCT SPECIFICATIONS:**

Weave: Woven black HDPE scrim

Coating: LLDPE 2.4 mil average each side (57g/m²/side) Colour: White, black or other colored coatings available

Weight  $9.1 \text{ oz/yd}^2 (309/\text{m}^2) \pm 5\%$ 

## **PERFORMANCE PROPERTIES:**

The following data are typical values based on ASTM standard tests. This data should not be considered specification.

Thickness ASTM D1777	Nominal 24 mil (0.60 mm), ± 10%
Grab Tensile (N)	MD 294 lb (1350)
ASTM D7004	TD 242 lb (1074)
Strip Tensile (N/5cm)	MD 240 lb/in (2131)
ASTM D7003	TD 270 lb/in (2398)
Tongue Tear-large scale (N)	MD 90 lb (400)
ASTM D5884	TD 92 lb (408)
Mullen Burst ASTM D751	530 psi (3652 kPa)
MVTR	
ASTM E96 Proc. BW	0.34 g/m <sup>2</sup> ·24hr (0.05 perms)
Hydraulic Conductivity (Permeability)	1.77 x 10 <sup>-12</sup> cm/s
Calculated from MVTR	
Hydrostatic Resistance	262 psi (1805 kPa)
ASTM D751	202 psi (1005 ki u)
Puncture Resistance	150 lb (666 N)
ASTM D4833	
CBR Static Puncture	993 lb (4409 N)
ASTM D6241	· · ·
Dimensional Stability	MD -3.6%
ASTM D1204	TD -1.0%
Low Temperature Flex ASTM D2136-94	MD & TD: Pass @ -65°F (-85°C)
HP-OIT	
ASTM D5885 (Measured on coating formulation)	1071 minutes
Accelerated UV Weathering	000/ harralla atuan ath after 40 000 liabt barra
ASTM D7238	>90% tensile strength after 10,000 light hours

MD = Machine Direction. TD = Transverse Direction i Q.U.V [A-340 Lamps]; 20 hrs UV @ 75°C; 4 hrs condensation @ 60°C

These values are typical data and are not intended as limiting specifications.

This data is provided for informational purposes only. Titan makes no warranties as to the suitability or the fitness for a specific use or merchantability of the products referred to, no guarantee of satisfactory results from reliance upon contained information or recommendations and disclaims all liability from resulting loss or damage. This information is subject to change without notice, please check with us for current updates.